

ATL® Formula & Sports Racer Bladders

"Wedges" and "Pods"

FT3, FT3.5



FIA/SCCA Approved ATL builds hundreds of Formula and Sports Racer bladders each year, and many of those are custom sizes and shapes. If you have a unique bladder requirement, simply call ATL and speak to one of our Sales Engineers. We will be happy to build a fuel cell to your exact dimensions and specifications.

FC150 Wedge Bladder
5 Gal.

FB181 SCCA Spec Racer Bladder
7 Gal.



FC142 & FC160 "Pod" Bladder
4 and 6 Gal.



Aluminum Containers Available for Pods Too! Add -AC to bladder part#.



FC140-AC Wedge Cell
4 Gal.



Shown with Optional Aluminum Wedge Container Add 1/4" per Dimension For Aluminum Container

Apx Capacity Gal	Bladder Part#	Wt. Lbs.	(Nominal) Dimensions (in)				Filler Neck "	Vent Valve	Pick Up
			A	B	C	D			
4	FC140	3.4	4.0	8.0	11.0	15.0	2-1/4	#6AN	#6AN
5	FC150	4.3	4.0	9.0	15.0	16.0	2-1/4	#6AN	#6AN
5	FC152	4.3	4.0	9.0	17.0	14.0	2-1/4	#6AN	#6AN
7.5	FC157	6.4	4.0	9.0	15.0	24.0	2-1/4	#6AN	#6AN
4	FC142	3.6	4.0	8.0	30.0		2-1/4	#6AN	#6AN
6	FC160	4.6	5.0	8.0	36.0		2-1/4	#6AN	#6AN
7	FB181	6.3	SCCA Spec Racer Bladder With Foam & Nut-Ring. Fill Plate Not Included						

ATL World Rally Championship Cells FIA, WRC, SCCA Pro Rally, etc.

Mitsubishi Lancer EVO Series Bladders

Available for: EVO 4, 5, 6, 7, 8, 9, 10.

FIA FT3 Spec or 3.5



#171610 Subaru Impreza WRX Bladders

FIA FT3 Spec or 3.5



70 Liter Capacity with Surge-Tank & Guide Vanes.

ATL Off-Road & Rally Raid Fuel Cells

FT3



SP144-DX
44 Gal. Shown


"Desert Express"™

Designed for use in the punishing Off-Road Racing environment.

- Race-proven Hard-Rubber Bladder
- Durable .093" Thick Aluminum Container
- TF702 Quick-Fill Valve
- Double-Seal Fill Plate Gasket
- Optional EFI Package Available



TF702 Quick-Fill, Off-Set, "Paddle-Valve"™ Assembly



Adjustable 3" Quick-Fill Neck & Valve, 1-1/2" Vent Valve 90° and #8 Outlet.



"Rally Raid"

ATL'S Rally Raid Cells are constructed in FIA/FT3-1999 approved fabric. Each ATL Rally Raid Cell is supplied fully foam baffled with a centrally mounted internal collector, and is also supplied with an ATL 6x10 standard nut-ring fitted with (1) 57mm (2-1/4) x 45° Filler neck (with integral FIA valve (TF519), 1 x Level Gauge (KS144), 1 x -6 Fuel Outlet, 1 x -6 Fuel Return and 1 x -6 Rollover Vent Valve (TF350).



U.S. Gal Approx.	Complete Cell Part#	Wt. Lbs.	(Nominal) Outside Dimensions		
			L"	W"	H"
44	SP144-DX	38	26.00	26.00	17.00

For Bladder Only, See Pg. 13

U.S. Gal Approx.	Liters Approx.	Complete Cell Part#	(Nominal) Outside Dimensions			Wt. Lbs.
			L"	W"	H"	
53	200	RR200	39.3	19.7	16.1	22.25
79	300	RR300	39.3	27.5	17.7	30.25
105	400	RR400	47.2	34.5	15.7	38.00

Add AC For Aluminum Container

Toll Free: 1-800-526-5330

www.atlfuelcells.com