

ATL® Parts & Accessories

Level Senders, Gauges, Hoses & Racing Accessories



ATL Fuel Level Kits

ATL Fuel Level Kits can be installed in most Fuel Cells. When purchasing an ATL Fuel Probe separately, please contact an ATL Sales Engineer for the proper length & OHM range. Refer to DS448, DS444-AD, and DS 584 Installation Instruction Sheets.



Micro-Controller Style

NEW!
Enclosed Float Style With Low-Level Warning



Lighted Fuel Gauge KS116

240-33 Ohm.
2.25" Outside Diameter and mounts in a 1.875" Diam. hole



High-Level Indicator Kit KS109H
12 Volt, LED

Low-Level Indicator Kit KS109L
12 Volt, LED



AN Fittings

Bulkhead Assembly
TF204 AN #6 (3/8") Straight
TF232 AN #8 (1/2") Straight
TF170 AN #10 (5/8") Straight
Other Sizes Available, Please Inquire

Fuel Fill & Vent Hose Sold Per Foot - Hose Sizes by I.D.

- **RF103** 2-1/4" Reinforced Black Hose
- **RF118** 2-1/4" O.D. Aluminum Tube
- **RE213** 2" Corrugated Refueling Hose
- **RE155** 2" Corrugated Vent Hose
- **RE214** 1-1/2" Refueling Hose
- **RF131** 2-1/2" Clear Hose
- **RF102** 2-1/4" Clear Hose
- **RE162** 1-1/2" Clear Vent Hose
- **RE140** 1-1/4" Clear Vent Hose
- **RE118** 1" Clear Vent Hose



Flex Elbows

- RF128** Elbow 45°, 2-1/4" i.d.
- RE128** Vent Elbow 90°, 1" i.d.
- RF132** Black Elbow 45°, 2-1/4" i.d.
- RF133** Black Elbow 90°, 2-3/8" i.d.
- RF138** Elbow Reducer 45°, 2-1/4" i.d. to 1-1/2" i.d.

MicroController-Based, Capacitance Level Sensing Probe. Cut length to fit. No adjustment screws.

Fuel Level Kit Part#	Fuel Level Probe Only	Probe (in.) Length	OHMs Empty	OHMs Full	Popular Uses
KS143	KS146	4-12	240	33	Std. ATL
KS144	KS147	12-24	240	33	Std. ATL
KS159	KS157	24-36	240	33	Custom
KS160	KS158	36-48	240	33	Custom
N.A.	KS170	4-12	0	90	G.M.
N.A.	KS171	4-12	70	0	VDO
N.A.	KS172	12-24	0	90	G.M.
N.A.	KS173	12-24	70	0	VDO

NEW! Enclosed, Float-Style Level Sensing Probe. Fixed length (Do Not Cut). Factory calibrated.

KS 215K-8	KS 210-8	8"	240	33	Std. ATL
KS 215K-9	KS 210-9	9"	240	33	Std. ATL
KS 215K-10	KS 210-10	10"	240	33	Std. ATL
KS 215K-12	KS 210-12	12"	240	33	Std. ATL
KS 215K-13	KS 210-13	13"	240	33	Std. ATL
KS 215K-14	KS 210-14	14"	240	33	Std. ATL

ATL "DryCell" Desiccant Drier TF629


Attaches to fuel cell vent hose and excludes moisture. A must for preventing phase separation in ethanol-oxygenated gasolines.
7" Overall, 5-1/2" In-Line



See ATL Bulletin #DS571 & DS577

Heavy Duty Gaskets


- TF217-W** 6"x10" (Wide) 24 Bolt
- TF217-T** 6"x10" Thin 24 Bolt
- TF217** 6"x10" Obround 24 Bolt
- TF236** 4"x6" Obround 12 Bolt
- TF147** 4-3/4" B.C. 12 Bolt
- TF148** 3" B.C. 6 Bolt
- TF653** Vent Valve 2-1/2" B.C. 8 Bolt
- TF467** Level Probe 5 Bolt
- TF510** 2-1/8" B.C. 6 Bolt



Seal Kit KS161
Gaskets, Seals, Flapper, Bolts & Washers. For TF193, A; 184, A, S; 183, A, S



Seal Kit KS162
Gaskets, Seals & Flap Valve. For TF195 & TF600



Dip Sticks

- TF265** #6 Dip Stick Kit Includes: TF204 AN #6 Bulkhead, TF207 16" DipStick, You Cut to Length
- TF627** AN#10 Alky-Tube DipStick Assembly



Volume Displacement Products

Install in Fuel Bladder to Reduce Capacity - Nominal Sizes

- VD50** 50mm .02 Gal. Ball
- VD70** 70mm .05 Gal. Ball
- VD100** 100mm .14 Gal. Ball
- VD150** 150mm 0.5 Gal. Ball
- VD325** 0.5 Gal. Bladder 7"x4"x4"
- VD326** 1.0 Gal. Bladder 8"x8"x4"
- VD327** 2.0 Gal. Bladder 10"x8"x6"
- VD328** 2.5 Gal. Bladder 10"x10"x6"
- VD330** .75 Gal. V.D. Block 5.5"x5.5"x6"
- VDM01** VDO Mesh Sack for 100-150mm Balls
- VDM02** VDO Mesh Sack for 50-70mm Balls